

linea classic

classic reliability,
design and value.



Available Configurations: EE | AV

Available Number of Groups: 1 | 2 | 3 | 4

The clean lines and charm of the Linea Classic occupies many of the cafes, roasteries, and chains whose names have defined the industry. The Linea Classic has helped to forge the world of coffee over the last 3 decades. Built to embody the spirit of three words, reserved, reliable, and consistent, the Linea Classic S

can be trusted to be a dependable partner in any coffee program. New features provide baristas an easier coffee making experience, while also increasing the reliability of a machine which has already set the standard in the industry. The Linea Classic S can be equipped as

optional with a water sensor that measures the conductivity and hardness of water as it enters the machine. This information allows the user to monitor water quality and verify filtration performance without the need for additional testing tools.

Dual Boilers

Separate boilers optimize espresso brewing and steam production.

Saturated Groups

Ensure unsurpassed thermal stability, shot after shot.

Barista Lights - Special Order

Led lighting allows you to focus on your extraction and the cup.

Programmable Doses - AV only

Auto-volumetrics ensure repeatability and consistency in high-volume settings.

Autosteam - Special Order

Automatically stops the steam wand operation at a desired temperature.

Cup Warmer - Special Order

Maintain espresso and cappuccino cups evenly heated at a proper temperature.

Dual PID (coffee and steam)

Allows you to electronically control coffee and steam boiler temperature.

3-button interface

Buttons of the left group (AV) or on the electronics board (EE) can be used to program the machine.

High Legs - Special Order

Makes it easier to access beneath the machine.

Insulated Boilers

Reduce energy consumption while contributing to temperature stability.

Pro App Compatible

Electronic board that will allow connectivity with the La Marzocco Pro App.

Personalized Colors - Special Order

Customizable colors based on the RAL color system, on request.

½ Turn Steam Valve

Steam valve fully opens in ½ turn, requiring less movement for the barista to steam milk.

Shot Timer - AV only

Placed on top of the control button, digital shot timer monitors the extraction time.

High Cup Rail - Special Order

Allows users to stack multiple layers of cups.

Specifications	1 group	2 groups	3 groups	4 groups
Height (cm/in)	44,5 / 17,5	44,5 / 17,5	44,5 / 17,5	44,5 / 17,5
Width (cm/in)	49 / 20	69 / 28	93 / 37	117 / 46
Depth (cm/in)	58,5 / 23	58,5 / 23	58,5 / 23	58,5 / 23
Weight (kg/lbs)	41 / 90	59 / 130	73 / 164	107 / 236
Voltage	-	200V Single Phase	200V Single Phase	200V Single Phase
		220V Single Phase	220V Single / 3 Phase	220V Single / 3 Phase
		-	380V 3 Phase	380V 3 Phase
Wattage (min)	2500	3350	4930	6930
Wattage (max)	-	5670	7790	9470
Coffee Boiler Capacity (liters)	1,8	3,4	5	2 x 3,4
Steam Boiler Capacity (liters)	3,5	7	11	15